

TORO**Count on it.****DirtCub™****F E A T U R E S**

Stake Pockets – Sidewall pockets allow for your own removable side extensions to increase box volume for maximum capacity of lighter-weight materials.

Hinged Tailgate – The DirtCub's reinforced tailgate provides a solid extension for longer loads and for placing pallets with a forklift.

Balanced Design – Uniquely engineered to maintain a stable tongue weight - even when the bed is fully elevated.

Walking Beam Suspension – All four tires maintain contact with the turf regardless of the terrain and the payload weight remains evenly distributed on a 64" (1.6m) wheelbase - minimizing any footprint.

Adjustable Hitch – The fully adjustable hitch height allows the unit to be towed by a variety of heavy-duty utility vehicles.

Hydraulic Cylinder – Variable control of the lift cylinder allows for gradual raising of the bed and provides over 50 degrees of dump angle.

Double the work in half the time.

The DirtCub utility dump box trailer enables twice the capacity in one trip and cuts the number of trips required to transport material in half. Use when the utility vehicle bed is occupied with other job materials or another attachment, such as a topdresser or sprayer. Transport and dump up to 1360 kg (3000 lbs) of material in the 1.5 m x 1.7 m (5' x 6') bed. The DirtCub is designed to be towed by utility vehicles, no tractor required. Provides stability and maneuverability even under heavy loads. The 4-wheel walking beam suspension provides very light foot print on sensitive surfaces.



DirtCub Hydraulic Dump Box Trailer
- Shown with optional Universal Tool Holder

DirtCub™ Specifications



DIRTCUB, MODEL 44720*	
Hydraulic Dump Box	Bed Size: width: 1.54 m (60 13/16") length: x 1.78 m (70 1/8") Unit Size: width: 1.73 m (68 1/8") height: 1.16 m (45 9/16") Weight: 437 kg (956 lbs.) Payload: 1360 kg (3000 lbs.) Suspension: 4 wheel walking beam Tire Size: 60 cm x 32.5 cm x 30 cm (24" x 13" x 12"), 4 ply Inflation: 124 kPa (18 psi)
Tow Vehicle Requirements	Towing Capacity (max. payload): 1,550 kg (3,400 lb) Tongue Weight (max. payload): 136 kg (300 lb) Minimum Power: 13 kW (18 hp)

©2010 The Toro Company

8111 Lyndale Ave. S.,
Bloomington, MN 55420-1196.

Specifications subject to change. Please contact your Toro distributor for details.

Printed in the U.S.A.

GB 200-XXXX