

**TORO****Count on it.**

# MH-400

## F E A T U R E S

**Accurate** – Intuitive settings and operating system deliver a perfect spread every time. Repeatable settings for consistent performance and defined edges.

**Wireless Remote Operation** – Available wireless controller allows real-time adjustments. Make quick setting changes and store settings for future use. Base model features a wired controller.

**Spread Consistency** – Ultra Light to Ultra Heavy - Evenly apply materials from 2.74 m (9') narrow to 10.67 m (35') wide with the use of our unique "drop zone" patented sliding adjustment.

**Dependable** – All-steel construction, heavy duty components and low maintenance provide long life and reliable performance.

**Versatile** – The twin spinner accessory can be swapped out with a 270 degree swivel cross-conveyor quickly and easily without tools. Elevate the rear to a height of 2 m (6') and fill the ProPass topdresser with material, or use as a multi-purpose dump trailer. Optional brakes available.

## The Original Material Handler. And Then Some.

The large capacity MH-400 delivers versatility and performance to tackle a wide range of jobs at any facility. The cross conveyor is ideal for completing bunker and greens renovations, cart path rebuilding, applying mulch, back filling of drainage ditches, and much more. Install the twin spinner accessory and the MH-400 becomes a large area topdresser to transport and accurately spread materials ranging from crumb rubber, to fertilizer, to a sand/peat topdressing mix. The rear hitch receiver allows implements, such as a wood chipper, to be towed in tandem. An integral component of any maintenance program, the efficient MH-400 reduces labor, saves time and cuts operating costs.



Twin spinner option

Chassis features a 4-wheel walking beam suspension for a light footprint on sensitive turf

# MH-400 Specifications



<b>MH-400, MODELS 44930 &amp; 44931 / MH-400 WIRELESS, MODELS 44933 &amp; 44934*</b>	
<b>GENERAL</b>	Hopper Capacity: 3.06 m <sup>3</sup> (4 yd <sup>3</sup> ) Main Conveyor Belt: One Piece Vulcanized, Self Tracking, 30" wide Controls: Standard Hydraulic (SH) or Electronic Hydraulic (EH)
<b>WEIGHT</b>	Base Model: 1,360 kg (3,000 lbs) - empty with no options installed
<b>CHASSIS</b>	Payload (tare): 5,353 kg (11,800 lbs) GVWR: 6,713 kg (14,800 lbs) Suspension: 4 Wheel Walking Beam with 10 ply turf tires Tire Size: 82.5 cm x 40 cm x 40.25 cm (33" x 16" x 16.1") 10 ply Brakes (electric) - Optional 2 or 4 wheel
<b>DIMENSIONS</b>	Length: 4.8 m (190") Height: 2.2 m (86") Width: 1.98 m (78")
<b>TOW VEHICLE REQUIREMENTS</b>	Towing Capacity: 7,175 kg (15,850 lbs) - maximum payload Minimum Power: 34 kW (45 hp)
<b>HYDRAULICS</b>	Recommended Flow (min no options installed): 23 l/min (6 US gal/min) Recommended Flow (min options installed): 38 l/min (10 US gal/min) Recommended Input Pressure (min): 138 Bar (2,000 PSI)
<b>WARRANTY</b>	Two-year limited warranty. Refer to operators manual for further details.
<b>CE REQUIREMENTS</b>	Meets the CE requirements for the EU

©2010 The Toro Company

8111 Lyndale Ave. S.,  
Bloomington, MN 55420-1196.

Specifications subject to change. Please contact your Toro distributor for details.

Printed in the U.S.A.

**GB** 200-XXXX